

PALLET STRETCH WRAPPER POWER PRE-STRETCH MODEL EXP-108



STANDARD FEATURES:

- 300% power pre-stretch
- Home position: the turntable always stops at the same position.
Height seeking by photo sensor.
- Wrapping tension/turntable speed/carriage speed are adjustable.
- A metal embossing pre-stretch roller. No maintenance required.
- Automatic firm cut off at cycle end.
- Automatic film Pin Puncture
- 180° Rotating control box
- Adjustable top and bottom wrap counts
- Turn table diameter 1500mm
- Fully automatic, pre-programmable wrapping cycles – 3 off.
- Reinforce button for awkward loads.
- Both one touch automatic program and manual run are available.
- Advanced soft wrapping device on the package available.
- Soft start and stop.
- One way idle roller to keep the film outside the carriage if it is broken.
- Easy film threading device
- 12 pieces alloy plastic castor to support the turntable.
- Trouble shooting shown on screen
- Height detection by photo sensor
- Max load weight 1650kg

OPTIONS:

- Top pressure plate driven by DC motor.
- 1.65m & 1.8m dia. Turntable (load weight 1650kg & 2000kg)
- 2.5m & 3.0m wrapping height.
- Ramp.
- Horse shoe turn table 1.65m Diameter (max load weight 1200kg)

EXP-108 SPECIFICATIONS

| | |
|----------------------|--------------------------|
| Max. wrapping height | 2,000mm (80") |
| Max. turntable speed | 12 rpm |
| Max. loading weight | 1650kg & 2000kg |
| Film roll width | 500mm (20") |
| Film roll outer dia. | 250mm (10") |
| Film core inner dia. | 76mm (3") |
| Power supply | 240V Single phase 10A |
| Power Consumption | 1.2kw |
| Turntable motor | 1/2 HP 220V AC - 3 phase |
| Carriage motor | 1/2 HP 220V AC - 3 phase |
| Power pre-stretch | 1/2 HP 220V AC - 3 phase |

